



Revision Number: 003.2

Issue date: 01/06/2014

1. PRODUCT AND COMPANY IDENTIFICATION

| | | | |
|-------------------------------|-----------------------------------|---------------------|---------------|
| Product name: | Nickel Grade Anti-Seize | IDH number: | 235028 |
| Product type: | Lubricant | Item number: | 77124 |
| | | Region: | United States |
| Company address: | Contact information: | | |
| Henkel Corporation | Telephone: 860.571.5100 | | |
| One Henkel Way | Emergency telephone: 860.571.5100 | | |
| Rocky Hill, Connecticut 06067 | Internet: www.henkelna.com | | |

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

| | | | |
|------------------------|-----------|--|--------------------|
| Physical state: | paste | HEALTH: | 1 |
| Color: | grey | FLAMMABILITY: | 1 |
| Odor: | Petroleum | PHYSICAL HAZARD: | 0 |
| | | Personal Protection: | See MSDS Section 8 |
| WARNING: | | MAY CAUSE EYE IRRITATION. | |
| | | MAY CAUSE ALLERGIC SKIN REACTION. | |

Relevant routes of exposure: Skin, Eyes

Potential Health Effects

| | |
|----------------------|--|
| Inhalation: | Vapors may cause headaches, nausea, dizziness and respiratory tract irritation. |
| Skin contact: | May cause allergic skin reaction. Repeated or prolonged contact may lead to skin irritation, dermatitis or oil acne. |
| Eye contact: | Contact with eyes will cause irritation. |
| Ingestion: | Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |

Existing conditions aggravated by exposure: Eye disorders. Skin disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous components | CAS NUMBER | % |
|-----------------------------------|-------------|---------|
| Petroleum Distillates | Proprietary | 30 - 60 |
| Nickel | 7440-02-0 | 10 - 30 |
| Graphite | 7782-42-5 | 10 - 30 |
| Sodium petroleum sulfonates | Proprietary | 1 - 5 |
| Aluminum not powder, dust or fume | 7429-90-5 | 1 - 5 |

4. FIRST AID MEASURES

| | |
|----------------------------|--|
| Inhalation: | If symptoms develop and persist, get medical attention. Move to fresh air. |
| Skin contact: | Wash with soap and water. If symptoms develop and persist, get medical attention. |
| Eye contact: | In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention. |
| Ingestion: | Aspiration may cause pulmonary edema and pneumonitis. Do not induce vomiting. Get medical attention. |
| Notes to physician: | Aspiration may cause pulmonary edema or aspiration pneumonia. |

5. FIRE FIGHTING MEASURES

| | |
|--|---|
| Flash point: | > 93 °C (> 199.4 °F) |
| Autoignition temperature: | Not available. |
| Flammable/Explosive limits - lower: | Not available. |
| Flammable/Explosive limits - upper: | Not available. |
| Extinguishing media: | foam Dry chemical. Carbon dioxide. |
| Special firefighting procedures: | None |
| Unusual fire or explosion hazards: | None |
| Hazardous combustion products: | Metal vapors. Oxides of carbon. Oxides of aluminum. Oxides of nickel. |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| | |
|-----------------------------------|--|
| Environmental precautions: | Prevent further leakage or spillage if safe to do so. Contain spill. |
| Clean-up methods: | Store in a partly filled, closed container until disposal. Scrape up as much material as possible. |

7. HANDLING AND STORAGE

| | |
|------------------|---|
| Handling: | Use only with adequate ventilation. Do not get on skin or clothing. Do not breathe gas/fumes/vapor/spray. Wash thoroughly after handling. |
| Storage: | Store away from heat, sparks, flames, or other sources of ignition. Keep in a cool, well ventilated area. Keep container closed. |

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous components | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|-----------------------------------|---|--|-----------|-------|
| Petroleum Distillates | 5 mg/m ³ TWA Inhalable fraction. 5 mg/m ³ TWA mist 10 mg/m ³ STEL mist | 5 mg/m ³ TWA mist 500 ppm (2,000 mg/m ³) PEL 5 mg/m ³ PEL Mist. | None | None |
| Nickel | 1.5 mg/m ³ TWA Inhalable fraction. | 1 mg/m ³ PEL (as Ni) | None | None |
| Graphite | 2 mg/m ³ TWA Respirable fraction. | 5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust. 15 MPPCF TWA | None | None |
| Sodium petroleum sulfonates | None | None | None | None |
| Aluminum not powder, dust or fume | 1 mg/m ³ TWA Respirable fraction. | 5 mg/m ³ PEL (as Al) Respirable dust. 15 mg/m ³ PEL (as Al) Total dust. | None | None |

Engineering controls:

Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Observe OSHA regulations for respirator use (29 CFR 1910.134). Use a NIOSH approved supplied air respirator with an organic cartridge if the potential to exceed established exposure limits exists.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Neoprene or oil resistant gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|-----------------------------|
| Physical state: | paste |
| Color: | grey |
| Odor: | Petroleum |
| Odor threshold: | Not available. |
| pH: | Not available. |
| Vapor pressure: | < 5 mm hg (80 °F (26.7 °C)) |
| Boiling point/range: | Not available. |
| Melting point/ range: | Not available. |
| Specific gravity: | 1.1 |
| Vapor density: | Not available. |
| Flash point: | > 93 °C (> 199.4 °F) |
| Flammable/Explosive limits - lower: | Not available. |
| Flammable/Explosive limits - upper: | Not available. |
| Autoignition temperature: | Not available. |
| Evaporation rate: | Not available. |
| Solubility in water: | Negligible |
| Partition coefficient (n-octanol/water): | Not available. |
| VOC content: | 2.47 %; 27 g/l |

10. STABILITY AND REACTIVITY

| | |
|--|--------------------------|
| Stability: | Stable |
| Hazardous reactions: | Will not occur. |
| Hazardous decomposition products: | No data |
| Incompatible materials: | Strong oxidizing agents. |
| Conditions to avoid: | No data |

11. TOXICOLOGICAL INFORMATION

| Hazardous components | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|-----------------------------------|----------------|-----------------|--|
| Petroleum Distillates | No | No | No |
| Nickel | No | No | No |
| Graphite | No | No | No |
| Sodium petroleum sulfonates | No | No | No |
| Aluminum not powder, dust or fume | No | No | No |

| Hazardous components | Health Effects/Target Organs |
|-----------------------------------|--|
| Petroleum Distillates | Irritant |
| Nickel | Allergen, Carcinogen, Irritant, Kidney, Mutagen, Reproductive, Respiratory |
| Graphite | Lung |
| Sodium petroleum sulfonates | No Target Organs |
| Aluminum not powder, dust or fume | Central nervous system, Irritant, Lung |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.
Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

| | |
|---------------------------|---------------|
| Proper shipping name: | Not regulated |
| Hazard class or division: | None |
| Identification number: | None |
| Packing group: | None |

15. REGULATORY INFORMATION

United States Regulatory Information

| | |
|---|---|
| TSCA 8 (b) Inventory Status: | All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. |
| TSCA 12 (b) Export Notification: | None above reporting de minimis |
| CERCLA/SARA Section 302 EHS: | None above reporting de minimis |
| CERCLA/SARA Section 311/312: | Delayed Health, Immediate Health |
| CERCLA/SARA Section 313: | This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Nickel (CAS# 7440-02-0). Aluminum not powder, dust or fume (CAS# 7429-90-5). |
| California Proposition 65: | This product contains a chemical known in the State of California to cause cancer. |

Canada Regulatory Information

| | |
|-----------------------------|---|
| CEPA DSL/NDL Status: | All components are listed on or are exempt from listing on the Canadian Domestic Substances List. |
| WHMIS hazard class: | D.2.B, D.2.A |

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Reviewed MSDS. Reissued with new date.

Prepared by: For Safety and Regulatory information contact: Regulatory Affairs Rocky Hill, CT 860-571-5204 Lou Fabrizio, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.